

Robex Asphalt Crack Filler

Rubberised bituminous crack filler for asphalt and tarmac.

Easy to apply by hand in most weather conditions and can be used for cracks up to 25mm (with the use of a filler).



Robex Asphalt Crack Filler

- Very good adhesion
- Excellent flexibility
- Ideal for cracks up to 3mm wide
- Cracks 3mm – 25mm can be filled by mixing a sand additive with the resin to form a mortar
- Can be used internally or externally

Robex Asphalt Crack Filler is a polymer modified, pourable rubberized bitumen for filling cracks in concrete. On its own it can be used on cracks up to 3mm, for wider cracks and joints (up to 25mm) sand can be added to bulk out the resin.

• Preparation

Work should not be carried out in wet or frosty weather. Surfaces must be dry or damp (no standing or running water) and be clean and free from dust, oil and fuel spillages.

• Application

Cracks up to 3mm: - Pour the Asphalt Crack Filler into the crack using a spouted can. Any surplus on the surface should be brushed or squeegeed out to a thin film and dusted over after drying with cement or very fine sand to remove the tack.

Cracks 3mm – 25mm: - Prime the sides of the crack with a brush coat of Asphalt Crack Filler. Fill the crack with a mortar made by mixing Asphalt Crack Filler with Robex sand additive in the ratio of one to one. Compact the mortar into the crack and smooth the surface with a trowel. After drying, apply a brush coat of Asphalt Crack Filler and blind this, after drying, with cement or sand.

• General Notes

Asphalt Crack Filler sets by the evaporation of water from the product. Application should only be carried out in good dry conditions. A rain resistant set will be delayed if the weather is cold, damp or humid. If stored in cold conditions Asphalt Crack Filler will thicken and become difficult to use. Ideally store at room temperature. Protect from frost.

• Coverage

5kg should fill approximately 100 metres of a 5mm wide crack

• Cleaning

To clean brushes, equipment, contaminants, etc., we recommend the use of Robex Cleaning Solvent RX117

• Health and Safety

Please refer to the relevant Material Safety Data Sheet.