Robex

Call us now on **01462 422 260** for a **FREE** site survey

Robex Non-Slip Concrete Floor Paint

Easy to apply by brush or roller the fine aggregate is suspended in the coating to give a nice even anti-slip finish.



Robex Non-Slip Concrete Floor Paint

- Quick drying and easy to apply
- Resistant to oils
- Hard wearing
- Mid gloss Finish

Standard Colours



Preparation

New concrete should be at least 28 days old or the moisture content less than 5%. All floors must be thoroughly dry and clean, vacuum shot blasting is recommended especially on old dense floors.

Preparation

Acid etching on floors is not recommended with moisture curing products as the extra dampness imparted by this process can detract from the 'key'. Should it be necessary to use Robex Power Prep E prior to coating, the concrete must be rinsed thoroughly with water and allowed to dry. It is important that no moisture is present before application.

Mixing Ratio

Single pack, however, contents must be stirred thoroughly prior to use.

Application

May be applied by brush or roller. Once initial mixing has been carried out and allowed to stand for 5 minutes. The aggregate is supplied separately and you can therefore decide on the level of non slip required. For a heavier non slip finish add all of the aggregate for a lighter non slip finish add less aggregate. We recommend trying a small sample prior to application. Adding Aggregate - add aggregate and continue to mix slowly. When the aggregate has been added the product should be applied immediately. We recommend periodically throughout application that the product be stirred to ensure the aggregate is evenly dispersed. Failure to do so will result in an uneven non-slip finish. Application should not take place in areas of high humidity or where condensation may occur on the uncured product.

Curing Time

Touch dry: 2 – 3 hours @ 20°c Hard dry: 12 hours @ 20°c Full Cure: 7 days @ 20°c

Coverage

40 – 50 m² per 5 litres per coat. Two coats normally required.

Storage

Store in cool, dry conditions away from direct sunlight.. Storage life is 12 months in original sealed containers

Cleaning

To clean brushes, equipment, contaminants, etc., we recommend the use of Robex Cleaning Solvent RX117

Health and Safety

Please refer to the relevant Safety Data Sheet.

27.7.16

No liability is accepted for any injury, loss or damage arising directly or indirectly from the use of the Company's products or from the information given in our data sheets, since the customer's use of the product is necessarily out of our control. The information given is intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that the products are suitable for their intended use