

## Robex Powerfloat Primer

An adhesion promoting primer for dense surfaces, Robex Powerfloat Primer is ideal for use under any of the Robex Epoxy range of floor coatings



**In Person:** Should you have any queries regarding product application, one of our trained sales engineers is always on hand to sort out any problems you may have.



**On line:** All of our technical data sheets and health & safety data sheets are available to download on line.



**On site:** If you would like Robex to apply your product for you call on the number below, we manufacture, we supply and we apply.



## Robex Powerfloat Primer

- Non-flammable
- Water based
- Bonds to damp surfaces
- Odour free

Robex Powerfloat Primer is a twin-pack epoxy resin primer for use on dense surfaces such as power floated concrete.

Powerfloat Primer can be used under or in conjunction with any Robex Epoxy Coating to help promote adhesion.

Standard Colours



## Robex Powerfloat Primer

- **Preparation**

New concrete should be at least 28 days old or the moisture content less than 6%.

Do not apply below 8°C.

The substrate should be clean and free from laitance, oil, grease and any other substance that may affect adhesion.

Compatibility checks should be undertaken if curing membranes have been used in the cure of the concrete.

- **Mixing**

Powerfloat Primer is supplied in pre-weighed containers and is ready for mixing on site. The individual components of the product should be stirred before the two are mixed together.

The entire component A should be added to curing agent B and mixed thoroughly for 5 minutes. The use of a paddle head mixer on a slow speed drill is recommended.

- **Application**

Application on all surfaces is by brush or roller ensuring complete coverage of the substrate.

- **Technical Specification @ 20°C**

Pot Life: 60 minutes

Time Before Recoating: 6 hours approximately

- **Storage Life**

12 months in original sealed containers.

Protect from frost.

- **Cleaning**

To clean brushes, equipment, contaminants, etc., we recommend the use of Robex Cleaning Solvent RX117.

- **Health & Safety**

Please refer to the relevant Health and Safety Data Sheet.

- **Robex Powerfloat Primer is primarily for use as a primer on power floated concrete surfaces, prior to the application of a Robex Epoxy Floor Coating.**

**In certain circumstances Powerfloat Primer can be used on other dense surfaces, for further information please contact our technical department.**

No liability is accepted for any injury, loss or damage arising directly or indirectly from the use of the Company's products or from the use of information given in our data sheets, since the customer's use of the product is necessarily out of our control. The information given is intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that the products are suitable for their intended use.