



Description

Robex Industrial Foam heavy duty closed cell foam is the answer to filling gaps in and around pipe work, ducting, insulation, flooring, door and window frames, roofing, roof / gutter joints and many other applications. Available in 750 ml canisters for use with the **Robex Foam Gun**.

Preparation

Surfaces should be clean, free from dust and loose particles, oil and grease. Immediately before application spraying of the surface with water will ensure even curing and maximum expansion. This should not be carried out if in the vicinity of electrical equipment / wiring.

Yield: 750 ml approx 36 ltrs

Curing Time

Tack free: approx 10 minutes

Touchable: approx 25 minutes

Curable time: approx 40 minutes

Full cure: approx 4 hours

Minimum Cure Temperature

5°C.

Application

Remove the clip on top of the black cap then screw on to the gun as far as the stop. Take care not to over-tighten or cross thread. Pull the gun trigger immediately, this will fill the body of the gun.

Pulling the trigger will then release foam. The size of beading emitted may be regulated using the adjusting screw above the gun handle.

Flash Point

NAV

Fire rating: DN4102/Part I - B2

Storage Life

9 months in original sealed containers at 15-20°C.

No liability is accepted for any injury, loss or damage arising directly or indirectly from the use of the Company's products or from the use of information given in our data sheets, since the customer's use of the product is necessarily out of our control. The information given is intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that the products are suitable for their intended use.

Tel + 44 (0)1462 422 260

Fax: + 44 (0)1462 422 262

The Robex Group Wilbury Way HITCHIN Hertfordshire SG4 0TY United Kingdom www.robex.co.uk