



Description

RX Line maker 2000 provides a cost effective solution for marking lines over large areas and is an exceptionally hardwearing system that can be applied internally or Externally.

Preparation

The surface for the line to be applied to must be clean, dry and free from grease, dust, dirt and peeling or loose materials or any other contamination.

RX Line Maker 2000 can be applied over existing paintwork providing it is hard and in good condition. However, some paints may lift or be softened when it is applied and it is advisable to check this by carrying out a test area.

Curing Time

Approximately 1 hour

Over coating

By brush after 4 hours

Application

Thoroughly mix RX Line Maker 2000 prior to application and then apply by brush or roller.

Minimum Cure Temperature

5°C

Coverage

14-20 m² per 2kg

Flash Point

Between 21°C and 55°C

Heat Resistance

Up to 65°C or for water immersed surfaces 43°C

Cleaning

To clean brushes, equipment, contaminants, etc., we recommend the use of **Robex All Purpose Cleaner**.

No liability is accepted for any injury, loss or damage arising directly or indirectly from the use of the Company's products or from the use of information given in our data sheets, since the customer's use of the product is necessarily out of our control. The information given is intended to serve as a guide only. Customers should satisfy themselves by appropriate trials that the products are suitable for their intended use.

Tel + 44 (0)1462 422 260

Fax: + 44 (0)1462 422 262

The Robex Group Wilbury Way HITCHIN Hertfordshire SG4 0TY United Kingdom www.robex.co.uk